

Economical Enhanced Wax Ribbon

TDW132

BARCODING THE WORLD

TDW132 is an economical enhanced wax ribbon. Its excellent scratch resistance, low printing energy consumption, and excellent printing quality can meet the strict requirements of various fields.


- Excellent Substrate Compatibility
- Excellent Scratch Resistance
- High Sensitivity & Definition

Printing Quality


Darkness



Sharpness



0° barcode




90° barcode



Min. printable character




Graphics




Sensitivity

Printing speed




Printing temperature



Resistance Test

Physical resistance

Slight exposure begins after approx. X cycles with a 680G weight load.



Substrate Compatibility

L3- ☐ < L2- ☒ < L1- ☒

Uncoated paper Writing Paper, Vellum ...	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Coated paper Art Paper, Art Printing Paper, High Gloss Paper	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Synthetic paper Synthetic Paper ...	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
Film label PP/PET/PE/BOPP/PVC (Low scratch resistance)	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
	TDW133	TDW121	TDW132

Water resistance test

The printed label was soaked in water at **100°C** for **2 hours** and then check whether the imprint of the label was significantly faded.



No significantly faded

Low-temperature test

The printed label was placed in a closed cold box at **-17°C** for **20 hours** and then check whether the imprint of the label was significantly fallen off.



No significantly fallen off

Recommended Applications



Receipt and delivery labels for warehouses



Logistics



Pharmaceuticals



Daily chemicals



Pre-packaging



Refrigeration Industry



Hot working



Retail labels



Digital & electronics labels



Clothing tags



Labels for automobile industry



Chemical industry



Nursery gardens and flowers



Production lines



Wooden products



Steel & iron manufacturing



Fixed assets



Electrical equipment



Mechanical equipment




Luggage

Properties

PET film	Ribbon
Thickness: 4.5μm	Thickness: 8.1±0.3μm
Ink	
Color: black Melting point: 70±3°C	
Storage condition	
Temperature: 5~35°C Humidity: 20~80% Validity period: 12 months	

Product Comparison



Certifications and Permits



ROHS2.0



REACH



ISO9001/14001



MSDS

HALOGEN

HALOGEN

Compatible With

- Zebra
- Datamax
- Intermec
- SATO
- other flat-head printings
- Honeywell
- Avery
- TSC
- Printronix

Economical Enhanced Wax Ribbon

TDW132

BARCODING THE WORLD



Hangzhou Todaytec Digital Co., Ltd.

All product specifications can be found at our website www.todaytec.com/en/

Marketing Department: +86 571-8577-1623

marketing@todaytec.com.cn

Add: 600 KangXin Rd, LinPing District, Hangzhou, Zhejiang Province, China